

Foam & Resin Cleaner

TLS-77

Removes Urethane Foam

Foam & Resin Cleaner TLS-77 was designed to remove urethane foam from equipment and tools. Blended for consumer safety without sacrificing performance.

Penetrates & Softens

Unlike methylene chloride based products that evaporate quickly, Foam & Resin Cleaner TLS-77 remains on the surface to penetrate and soften the foam. Sufficient time should be allowed for material to penetrate the surface before removing the loosened foam.

Safe

Foam & Resin Cleaner TLS-77 does not contain halogenated hydrocarbons, petroleum hydrocarbons, or flammable ingredients such as alcohols or ketones.



CLEANERS

Technical Data

appearance

clear liquid thick liquid

mild

odor

specific gravity rinsability

1.075 complete,

normal working conc. normal working temps use full strength ambient

Packaging Options

5 gallon pail 55 gallon drum 330 gallon tote tanks

Other Available TLS Products

ID 240

Industrial strength cleaner/degreaser

Shur Cool® 3830

Non-foaming full synthetic coolant for grinding, milling, drilling and other metalworking operations

Shur Cool ® 4045

Heavy-duty semi synthetic metalworking fluid



300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801 662.842.8143 · FAX: 662.842.8583 · 800.882.5966 www.tlspecialty.com · support@tlspecialty.com