

## RUST PREVENTATIVES

# Oxi Stop® 632

## Outdoor Metal Surface Protection

### Long Term Corrosion Protection

Oxi Stop® 632 is recommended for long term corrosion protection of all ferrous and non-ferrous metals.

### Dip, Spray, Brush, or Flow Coat

It is a solvent based product that can be applied by dip, spray, brushed or flow-coated. It leaves a thick, black, waxy film ideal for long term protection.

### Resistant to High Humidity & Salt Atmospheres

The residual film is highly resistant to high humidity and salt atmospheres, making Oxi Stop® 632 particularly useful for long-term indoor and outdoor storage applications.

#### Technical Data

chemical comp.	aliphatic hydrocarbons
appearance	clear, dark amber liquid
odor	bland
specific gravity	0.84
flash point	108°F
maximum solubility	negligible
normal working conc.	full strength
normal working temp.	ambient

#### Application

Auto Rustproofing to the following specifications:

Mil-C-83933A  
Mil-PFR 16173E Grade 4, Class 1

#### Packaging Options

5 gallon pail  
55 gallon drum  
330 gallon tote tanks

#### Other Available TLS Products

Shur Draw® 420  
Heavy-Duty semi synthetic drawing compound

Shur Cool® 5010  
Low-foaming top of the line synthetic coolant for steel, stainless steel and aluminium

ID 240  
Concentrated, industrial-strength liquid cleaner/degreaser.



**T & SPECIALTY**  
Chemicals for Industry

300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801  
662.842.8143 · FAX: 662.842.8583 · 800.882.5966  
WWW.TLSPECIALTY.COM · SUPPORT@TLSPECIALTY.COM