



## SPRAY CLEANERS

### Technical Data

chemical composition	phosphates, accelerators, and wetting agents
appearance	clear liquid
odor	mild
specific gravity	1.225 - 1.125
flash point	none
foaming tendency	slight
maximum solubility	complete
rinseability	good
biodegradable	yes
normal working conc	2% - 4% by vol
normal working temp	90°F - 100°F
pH @ normal working conc	3.5 - 5.5

# SpraKleen LT 750

## Heavy-duty, Detergent

### Low Temp Conversion Coating

Sprakleen LT-750 is a liquid, low temperature conversion coating used for cleaning and phosphating ferrous metals prior to painting.

### Remove The Toughest Of Soils

It is blended with an exceptionally hard working cleaning agent to help remove the toughest of soils.

### Aluminum, Zinc, and Stainless Steel

It may be used as an acid cleaner for aluminum, zinc, and stainless steel.

### Safe

Safe on steel, aluminum, & zinc. Attacks copper, brass, & magnesium  
Do not use on copper, brass, magnesium

### Packaging Options

5 gallon pail  
55 gallon drum  
330 gallon tote tanks or Bulk Delivery

### Other Available TLS Products

ID 240  
Industrial strength cleaner/degreaser.

Shur Draw<sup>®</sup> 420  
Heavy-Duty semisynthetic drawing compound

Oxi Stop<sup>®</sup> 2120  
A unique blend of wetting agents and corrosion inhibitors designed to give indoor rust protection on ferrous metals.



**T & SPECIALTY**  
Chemicals for Industry

300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801  
662.842.8143 · FAX: 662.842.8583 · 800.882.5966  
WWW.TLSPECIALTY.COM · SUPPORT@TLSPECIALTY.COM